Here's something to get PUMPED up about in portable gas detection.

Introducing the MGC Pump with a 5 day continuous run on a single charge.



6 month calibration cycle
Draw from up to 75 feet

Low maintenance

Stainless steel inlet

A New Option in Portable Gas Detection

Twice a day, every day... that's how often you have to charge most portable gas detectors, until now. Introducing the Multi Gas Clip Pump (MGC Pump) from Gas Clip Technologies, the only portable multi gas detector with an internal sampling pump that can go an entire work week without a charge.

A Long-Lasting Family Tradition

The MGC Pump follows in the long line of portable gas detectors by Gas Clip Technologies that last and last and last. Being able to go a long time between charges is a family tradition.

The Secret to a Long Life

Like our MGC, the MGC Pump uses low-power photometric technology to detect combustible gases (LEL) rather than ageold pellistor technology. The MGC Pump uses an IR source which conserves power and helps the battery last and last.

Ergonomic Design Makes for a Good Fit

The MGC Pump is also designed for comfort. The reduced, sloping shape of the holding area at the bottom of the instrument makes the MGC Pump a comfortable fit in the hands of your workers. It is fully submersible and simple to operate. The MGC Pump offers a one button design and the largest LCD screen in the industry so it's easy to read.

Calibrate the MGC Pump Once Every 6 Months

Other multi gas detectors require calibration anywhere from 1 to 3 months. The MGC Pump can go 6 months without being calibrated. This is an added benefit of IR sensing technology because IR is immune to pellistor sensor poisons such as silicone or H_2S .

Call Today or Visit GasClipTech.com

Get pumped up today and call Gas Clip Technologies at **1.877.525.0808** or visit gascliptech.com to learn more about the MGC Pump. After all, time is money.



Portable gas detectors you can count on. www.gascliptech.com ◆ Toll-free: 877.525.0808

Included with the MGC Pump:

10' Sampling Hose 10 Additional Filters; 5 Hydrophobic and 5 Particulate Stainless Steel Diffusion Stone



GCT IR Link



MGC Pump Dock

Part #	Description		
MGC-IR-PUMP	4 Gas Monitor containing IR sensor and internal pump		
MGC-P-PUMP	4 Gas Monitor containing Pellistor sensor and internal pump		
MGC-DOCK-PUMP	4 bay calibration and bump test station		
MGC-WMDOCK-PUMP	4 bay wall mounted calibration and bump test station		
MGC-DOCK-HP-PUMP	MGC PUMP 4 Bay Hi-Pressure Dock Station		
MGC-WMDOCK-HP-PUMP	MGC Pump 4 Bay Hi-Pressure Wall Mount Dock		
GCT-IR-LINK	GCT IR communication module w/USB cable		
Please	contact Gas Clip Technologies for additional		
	spares, accessories and gas.		

Distributed By:

EQUIPCO

Tel: +1 (888) 234-5678; +1 (925) 234-5678 Fax: +1 (925) 305-1300 2100 Meridian Park Boulevard, Concord, CA 94520

www.equipcoservices.com sales@equipcoservices.com

Specifications

-			
Size	5.7 x 3.0 x 1.5 in. (147 x 78 x 38.3 mm.)		
Weight	12.4 oz. (352g)		
Temperature	-4° to +122°F (-20° to +50°C)		
Humidity	5% to 100% RH (non-condensing)		
Battery Life	5 days continuous Pellistor: 30 hours continuous		
Charge Time	4 - 6 hours		
Alarms		udible (minimum 95 dB) Low, d OL (Over Limit), Pump	
LEDs	4 red alarm bar LEDs Yellow backlight (activated on button press) Red backlight (activated on alarm condition) Yellow Maintenance Notification LED		
Display	Alphanumeric Liquid Crystal Display (LCD)		
Logs	25 Bump tests 25 Events 25 Calibrations Continuous 1 second	nd data logging (> 2 month typical capacity)	
Tests	Full function self-te Sensors, battery an	est upon activation d circuitry conditions	
Ingress Protection	IP 67		
Gas Inlet	1/8" barbed fitting		
Certifications and Approvals	ECEX:	Class1, Division 1, Group A, B, C and D Class 1, Zone 0, AEx ia IIC T4 Ga C22.2 No.'s 0, 152, 157 Ex ia IIC T4 Ga IECEx CSA 14.0029 IEC 60079-0:2011, 60079-11:2011, 60079-26:2006 SIRA 14ATEX2120 CE (
-	InMetro: (pending)	EN50270 ANSI/ISA S12.13.01 UL-913 NCC xx-xxxxx Ex ia IIC T4 Ga (-20°C \leq Ta \leq 50°C)	
Pump Draw	Sample from up to	75 ft (23 m)	
Warranty	Full 2 years		
Gases	H₂S CO Combustible gas O₂	0 - 100 PPM (0.1 PPM increments) 0 - 500 PPM (1 PPM increments) 0 - 100% LEL (0.1% LEL increments) 0 - 30% vol. (0.1% vol. increments)	
Sensor Type	H₂S, CO, O₂: Single plug-in electrochemical cell Combustible: Plug-in infrared (IR) or pellistor		
User Options	User message	Maintenance notification	
	TWA/STEL intervals	5 TWA method	
pump	Languages (6)	Sensor enable/disable	
ternal pump	Pump test	SAFE display	
tation	Self-Test lock	Dock lock	
	Auto-zero on start	up Calibration gas	
	Bump test interval	Calibration interval	
	Low/High alarm	TWA/STEL alarm	
	-		



Portable gas detectors you can count on.

www.gascliptech.com \diamond Toll-free: 877.525.0808 2010-2014© Gas Clip Technologies, Inc. All Rights Reserved.