

A detailed photograph of a laboratory setup. In the foreground, a grey handheld gas leak detector, the ION GASCHECK G, is prominently displayed. The device has a small LCD screen at the top showing 'He 0.000500 ccfsec' and a control panel with buttons for 'Esc', up and down arrows, 'ZERO', and a power button. The background features a blue industrial machine with various components, including two pressure gauges on the left, several valves and pipes, and a control panel with a digital display and buttons at the top. The overall scene is brightly lit, suggesting a clean, professional laboratory environment.

# GASCHECK G


GAS LEAK DETECTOR

RAPID, ACCURATE DETECTION OF LOW  
LEVEL LEAKS.

[ionscience.com](http://ionscience.com)

Unrivaled Gas Detection.





**GASCHECK G RAPIDLY AND ACCURATELY DETECTS ALMOST ANY GAS OR GAS MIXTURE DOWN TO HIGHLY SENSITIVE LEVELS.**

## Best available leak detection

- Fast, accurate leak detection at highly sensitive levels
- Detects almost any known gas or gas mixture
- Particularly sensitive to ammonia, argon, butane, helium, hydrogen and SF6
- Reliable, stable, repeatable readings

## Ease of use

- Simple, one handed operation
- Large, clear LCD back lit display for easy viewing
- Graphical icon menu
- Conveniently calibrated against helium

## Flexibility

- Choice of readings in cc/sec, g/yr, mg/m<sup>3</sup>
- Easily upgradeable throughout the range

## Low cost operation

- Inexpensive consumables and parts
- 2 year warranty when instrument registered online





Designed for the search and location of gas leaks, GasCheck G has an advanced micro thermal conductivity sensor for fast, effective detection of almost any gas or gas mixture.

Robust and reliable, GasCheck G provides stable, repeatable readings of the detected gas. The instrument's LCD display, LED indicator and audible sounder clearly indicate the leak present.

GasCheck G automatically zeros to the ambient air around it when switched on and is ready to detect immediately. The instrument's easy to use graphical interface and intuitive keypad allows simple function, selection and adjustment.

Upgradeable throughout the range, GasCheck G is available in three distinct versions; G1, G2 and G3 with varied capabilities. Features can be easily added to upgrade the instrument without it having to be returned to the factory.

FEATURE	G1	G2	G3
Rapid detection of gas leaks	✓	✓	✓
Measure gas leaks (single gas)		✓	
Measure gas leaks (up to 20 gases)			✓
Audible sounder	✓	✓	✓
Flashing back-lit display	✓	✓	✓
Peak hold readings		✓	✓
Factory or custom calibration available		✓	✓
Data logging (store up to 10 readings)			✓
Readings displayed in cc/sec, g/yr, ppm or mg/m <sup>3</sup>			✓
Selectable battery type			✓
Upgradeable	✓	✓	

### Extend your instrument warranty

Your GasCheck G instrument warranty may be extended by simply registering your product on the Ion Science website within one month of purchase. Visit [www.ionscience.com/instrument-registration](http://www.ionscience.com/instrument-registration) to take advantage of this offer.

### Applications include

- Industrial
- Quality Assurance
- Manufacturing
- Laboratory
- Medical
- Research

### Accessories

GasCheck G is supplied with an exclusive range of accessories. Visit [www.ionscience.com/gascheck](http://www.ionscience.com/gascheck) for more information.



## Technical specifications

### DETECTOR

- Micro thermal conductivity detector (MTCD)
- Sensor is poison resistant with over range protection

### OPERATION

- Battery Type: 4 x alkaline AA size or NiMH (rechargeable)
- Typically 40 hours life

### SENSITIVITY (CC/SEC)

- He  $1 \times 10^{-5}$ , CH<sub>4</sub>  $5 \times 10^{-5}$ , R12  $5 \times 10^{-5}$ , Ar  $1 \times 10^{-4}$

### ACCURACY

- $\pm$  5% Displayed reading One digit

### RESPONSE

- T<sub>90</sub> = 1 second rise and clear down

### SOUND

- Flashing LED and 90 dBA (at 10 cm) audible sounder

### CALIBRATION

- Factory calibrated to fully documented procedures in accordance with our ISO 9001:2008 Quality Management System

### DATA LOGGING

- 10 data points (available for G3 only.)

### TEMPERATURE

- Operating: -20 to +60 °C, -4 to 140 °F
- Storage: -20 to +70 °C, -4 to 158 °F
- Humidity: 0 to 99% RH (non-condensing)

### FLOW RATE

- 2 cc/min

### WEIGHT & DIMENSIONS

- Instrument with probe: 390 x 60 x 49 mm, 15.5 x 2.3 x 1.9"
- Case: 420 x 320 x 97 mm, 16.5 x 12.5 x 3.8"
- Instrument: 0.45 kg, 1 lb, Packed 1.6 kg, 3.5 lb

GasCheck G V1.6. This publication is not intended to form the basis of a contract and specifications can change without notice.

EMC tested EN50081-1 & EN50082-1 July 98.

### Distributed by:

**ION Science Inc**  
4153 Bluebonnet drive,  
Stafford, Texas 77477

T Toll Free (877) 864-7710  
E [info@ionscienceusa.com](mailto:info@ionscienceusa.com)

“We have bought several GasCheck G3 units from Ion Science and are really happy with how reliable the ppm readings are – customers find the instrument easy to use. The customer service received from Ion Science is excellent, and so is the company overall.

**Lee Chamberlain, VP Operations, LACO Technologies**